

Double Angle V-Belt



Applications:
Conveyors
Mills
Cooling or
heating drums
& More

1 Double wrapped heavy duty fabric assures maximum resistance to heat, sunlight, grease, oil and dirt.


2 The core of the belt is made of a special blend of compounds to provide long life and superior horsepower capacity.

Recommended Sheaves:
Conventional – OD, Taper Bushed, or MST (B, C)

Heavy Duty V-Belts

Double Angle

V-Belt



Ideally suited for serpentine drives where power needs to be transmitted equally from both sides of the belt.



- Heavy-duty wrapped cover provides excellent resistance to abrasive wear, heat, ozone, grease, oil, or dirt
- Centrally located cord and special synthetic rubber compounds assure long v-belt life and smooth, capable horsepower capacity
- Available in AA, BB, and CC cross sections

Double Angle V-Belt Part Numbers

Part Number	Outside Circumference	Weight (lbs)
AA Section – Recommended Sheaves: Conventional – QD, Taper Bushed, or MST (B)		
AA51	54.3	0.40
AA55	58.3	0.43
AA60	63.3	0.47
AA62	65.3	0.49
AA64	67.3	0.50
AA66	69.3	0.52
AA68	71.3	0.53
AA70	73.3	0.55
AA75	78.3	0.58
AA78	81.3	0.61
AA80	83.3	0.63
AA85	88.3	0.66
AA90	93.3	0.69
AA92*	95.3	0.72
AA96	99.3	0.75
AA105	108.3	0.82
AA112	115.3	0.87
AA120	123.3	0.93
AA128	131.3	0.99
AA130*	133.3	1.00
AA131*	134.3	1.01
AA136*	139.3	1.05
AA148	151.3	1.14
BB Section – Recommended Sheaves: Conventional – QD, Taper Bushed, or MST (B)		
BB42*	46.5	0.57
BB43	47.5	0.58
BB45*	49.5	0.60
BB51	55.5	0.69
BB53	57.5	0.72
BB54	58.5	0.72
BB55	59.5	0.73
BB60	64.5	0.79

Double Angle V-Belt

Part Number Example: **AA51** = **AA** **51**
Cross Section Inside Circumference (inches)

Part Number	Outside Circumference	Weight (lbs)
BB Section – Recommended Sheaves: Conventional – QD, Taper Bushed, or MST (B)		
BB64	68.5	0.86
BB68	72.5	0.89
BB71	75.5	0.95
BB72	76.5	0.96
BB73	77.5	0.97
BB74	78.5	0.98
BB75	79.5	1.00
BB76	80.5	1.01
BB77	81.5	1.02
BB78	82.5	1.04
BB80*	84.5	1.06
BB81	85.5	1.07
BB83	87.5	1.10
BB85	89.5	1.13
BB89	93.5	1.18
BB90	94.5	1.19
BB91*	95.5	1.20
BB92	96.5	1.22
BB93	97.5	1.23
BB94	98.5	1.24
BB95	99.5	1.25
BB96	100.5	1.27
BB97	101.5	1.28
BB100	104.5	1.32
BB103	107.5	1.36
BB105	109.5	1.38
BB107	111.5	1.41
BB108	112.5	1.42
BB111	115.5	1.46
BB112	116.5	1.47
BB116	120.5	1.52
BB117	121.5	1.53
BB118	122.5	1.55

Part Number	Outside Circumference	Weight (lbs)
BB Section – Recommended Sheaves: Conventional – QD, Taper Bushed, or MST (B)		
BB120	124.5	1.57
BB122	126.5	1.60
BB123	127.5	1.61
BB124	128.5	1.62
BB128	132.5	1.68
BB129	133.5	1.69
BB130	134.5	1.70
BB131*	135.5	1.71
BB136	140.5	1.78
BB140	144.5	1.84
BB144	148.5	1.89
BB155	159.5	2.03
BB157	161.5	2.06
BB158	162.5	2.07
BB160	164.5	2.10
BB162	166.5	2.12
BB168*	172.5	2.20
BB169*	173.5	2.21
BB170	174.5	2.23
BB173	177.5	2.26
BB180	184.5	2.35
BB182	186.5	2.38
BB190	194.5	2.48
BB195	199.5	2.55
BB210	214.5	2.72
BB225*	229.5	2.90
BB226*	230.5	2.91
BB228	232.5	2.94
BB230*	234.5	2.96
BB240*	244.5	3.09
BB255	259.5	3.28
BB267*	271.5	3.43
BB270	274.5	3.47

Heavy Duty V-Belts

Double Angle

V-Belt

Double Angle V-Belt Part Numbers

Part Number Example: **CC75** = **CC** **75**
Cross Section Inside Circumference (inches)

Part Number	Outside Circumference	Weight (lbs)
BB Section – Recommended Sheaves: Conventional – QD, Taper Bushed, or MST (B)		
BB273*	277.5	3.51
BB277*	281.5	3.56
BB278	282.5	3.58
BB285*	289.5	3.67
BB300	304.5	3.86
BB360*	364.5	4.69
CC Section – Recommended Sheaves: Conventional – QD, Taper Bushed, or MST (C)		
CC75*	81.4	1.84
CC81	87.4	1.97
CC85	91.4	2.07
CC90	96.4	2.18
CC96*	102.4	2.32
CC105	111.4	2.53
CC112	118.4	2.69
CC119*	125.4	2.85
CC120	126.4	2.87
CC128	134.4	3.06
CC136*	142.4	3.24
CC144	150.4	3.43
CC148*	154.4	3.54
CC150	156.4	3.59
CC158	164.4	3.75
CC162	168.4	3.84
CC173	179.4	4.10
CC176*	182.4	4.17
CC180	186.4	4.27
CC195	201.4	4.62
CC210	216.4	4.97
CC225	231.4	5.27
CC240	246.4	5.62
CC255*	261.4	5.97

Part Number	Outside Circumference	Weight (lbs)
CC Section – Recommended Sheaves: Conventional – QD, Taper Bushed, or MST (C)		
CC270	276.4	6.32
CC300	306.4	7.01
CC330*	336.4	7.70
CC360	366.4	8.44
CC390	396.4	9.14
CC420	426.4	9.84

*Non-stock item. Minimum order quantity and/or extended lead times may apply. Contact customer service for availability.